

www.idp-corp.com

SMART-50 Series, manufactured by IDP Corporation, is highly engineered dye-sublimation ID card printers which provide you with maximum efficiency for the ID card printing.

SMART-50 Series is designed based on the flexible usage environment support. This makes you easy to choose printer and save initial investment. You can add not only flipper or laminator for dual side printing or laminating but also various encoders such as magnetic stripe, contact and contactess encoder. The enhanced FINE[™] Imaging Technology of SMART-50 Series enables to print high quality image. SMART-50 Series will be a perfect choice for ID card, membership card, access control card.

• Business Card

SmartTech ID Company Inc Telephone:+1 813-852-2010 FAX:+1 813-852-2523 www.smarttechid.com E-mail: info@smarttechid.com





SMART-50 series

SMART-50 Series, manufactured by IDP Corporation, is highly engineered dye-sublimation ID card printers which provide you with maximum efficiency for the ID card printing.

SMART-50 Series is designed based on the flexible usage environment support. This makes you easy to choose printer and save initial investment. You can add not only flipper or laminator for dual side printing or laminating but also various encoders such as magnetic stripe, contact and contactless encoder. The enhanced FINE[™] Imaging Technology of SMART-50 Series enables to print high quality image. SMART-50 Series will be a perfect choice for ID card, membership card, access control card, government ID, healthcare card and banking card.

IDP Corporation tries to open new era of ID card printer. You might experience what is real ID card printer.

Technology

- Clear Printing by FINE[™] Imaging Technology.
- Instant Direct Heating Mechanism for Lamination (SMART-50L).
- On-Site Upgradable Options for Dual Side Printing and Laminating.
- · Automatic and Manual Card Feeding.
- · On-Site Installable Encoders for Magnetic Strip, Contact and Contactless Smartcard.
- 64MB High Memory.

01

- · Automatic Ribbon Search and No Need for Sensor Calibration.
- Environment Friendly Rewritable Printing (SMART-50R).



- Compact and Optimized Design for Desktop Environment.
- 2 Lines LCD with 2 LED Buttons for Front Operation.
- Front Input and Output Hoppers.
- Easy TPH Replacement.
- · Drop-In Ribbon Cartridge.



- Smart SDK to Develop Customized Printing Applications Without Additional Cost.
- Smart Utilities to Check Working States and Adjust Configurations.
- On-Line Technical Support.


Issuance

Smart Applications ensure your card issuance and data management through SMART-50 series at no extra cost.

- Smart Design is a card design tool including magnetic stripe encoding function.
- · Smart DB is to manage issuing data conveniently and supports OBDC (Open Database Connectivity).
- · Customer's data such as facial images, signatures and scanned data can be improted to Smart DB and printed on a card at a time.



- Smart Network Module can not only print cards but also encode magnetic stripe, contact and contactless smartcard through the network.
- Smart Network Module has OCP (Open Card Print) Protocol which can encode and print cards using commands on all kind of platform and don't need to install printer driver and modify card issuance application using our SDK.



Data Security

SMART-50 Series provides the effective security features for the authentication and the data encryption.

- SMART-50 Series has the password verification function to provide root and user authentications.
- SMART-50 Series can set a specific authorized PC for encoding and printing cards.
- SMART-50 Series can encrypt data transmitted on USB and can support SSL (Secure Socket Layer) Protocol on Ethernet communication.

02

SMART-50 Series can build up the network printer server for encoding and printing cards.





SMART - 50S

Laminating ID CARD PRINTER SMART - 501

SMART-50L (Printing and Laminating)

- Single or Dual-side printing with Single or Dual-side Lamination.
- Instant Direct Heating Mechanism for Lamination.
- Enhanced Printing and Laminating Speed (23 sec. per card, YMCK and Single Lamination). Field Upgradable by Installation of Laminator on SMART-50S.
- 2 lines LCD with 2 LED Buttons for Front Operation. Holographic Lamination for Visual Security and Card Durability.
- Installable Encoder: Magnetic Stripe, Contact and Contactless Smartcard, SIM.
 Upgradable Module: Network.

Compact and Optimized Design,
 Enhanced Printing Speed (Max, 18 sec, per card, YMCKO).

300dpi with Edge-to-Edge Printing.

SMART-50S (Single-sided Printing

Single sided ID CARD PRINTER

- 2 lines LCD with 2 LED Buttons for Front Operation.
- Advanced Cleaning Roller.
- Low Cost Security with UV Printing.
- Installable Encoder: Magnetic Stripe, Contact and Contactless Smartcard, SIM,
- Upgradable Module: Flipper, Laminator and Network.

Experience SMART ID Card Printing Technology Feel the delicate Card printer solution from SMART!

- Overlay
- UV Panel
- 300dpi & Edge-to-Edge
- Contact
- Contactless
- Magnetic Stripe

• SMART-50D printed on both sides.

Dual sided ID CARD PRINTER




SMART-50D (Dual-sided Printing)

- Single or Dual-sided Printing.
- Enhanced Printing Speed (Max. 25 sec. per card. YMCKOK).
- 300dpi with Edge-to-Edge Printing.
- Field Upgradable by Installation of Flipper on SMART-50S.
- 2 lines LCD with 2 LED Buttons for Front Operation.
- Low Cost Security with UV Printing.
- Installable Encoder: Magnetic Stripe, Contact and Contactless Smartcard, SIM,
- Upgradable Module: Laminator(After Removing Flipper) and Network.

• Direct Thermal Rewritable Method, • 2 LED Buttons for Front Operation, • Enhanced Rewriting Speed (Max. 10 sec. per card).
 • Installable Encoder: Magnetic Stripe, Contact and Contactless Smartcard, • Upgradable Module: Network.

Experience SMART Rewritable Technology Bring you a cost efficient solution for rewritable cards!





Single Lamination). • Field Upgradable by Installation of Laminator on SMART–50S, nination for Visual Security and Card Durability. SIM, • Upgradable Module: Network,

Experience SMART Laminating Technology See the perfect SMART LAMINATOR for your Security!

- Lamination •
- UV Panel •
- 300dpi & Edge-to-Edge
 - Contact •

04

- Contactless •
- Magnetic Stripe •

Rewritable ID CARD PRINTER

IART - **50**R



Printer Specification

SMART–50 Series	e e			10	
	SMART-50S	SMART-50D	SMART-50L	SMART-50R	
	Single Side Card Printer	Dual Side Card Printer	Card Printer and Laminator	Re-Write Card Printer	
Printing					
Print Type	Dye - Sublimation	Dye - Sublimation	Dye - Sublimation	Thermal Transfer	
Print Area	Edge to Edge	Edge to Edge	Edge to Edge	Edge to Edge	
Resolution	300 dpi	300 dpi	300 dpi	300 dpi	
Dual Side Printing	Option (with Flipper)	Yes	Yes (Flipper Installed)	No	
Card					
Card Feeding	Automatic	Automatic	Automatic	Automatic	
Card Size	ISO CR80 (54mm x 86mm / 2.12" x 3.38")	ISO CR80 (54mm x 86mm / 2.12" x 3.38")	ISO CR80 (54mm x 86mm / 2.12" x 3.38")	ISO CR80 (54mm x 86mm / 2.12" x 3.38")	
Card Thickness	0.38mm (15mil) ~ 1.0mm (40mil)	0.38mm (15mil) ~ 1.0mm (40mil)	0.76mm (30mil) ~ 1.0mm (40mil)	0.38mm (15mil) ~ 1.0mm (40mil)	
Card Type	PVC, Composite PVC, PET	PVC, Composite PVC, PET	PVC, Composite PVC, PET	Rewriteable Themochromic Material	
Print Speed					
Monochrome	5 sec. (720 card / hour)	5 sec. (720 card / hour)	5 sec. (720 card / hour)	20 sec. (180 cards/hour) Max. 10 sec. (Max. 360 cards/hour)	
үмско	22 sec. (164 cards/hour) Max. 18 sec. (Max. 200 cards/hour)	22 sec. (164 cards/hour) Max. 18 sec. (Max. 200 cards/hour)	22 sec. (164 cards/hour) Max. 18 sec. (Max. 200 cards/hour)	,	
үмскок		30 sec. (120 cards/hour) Max. 25 sec. (Max. 144 cards/hour)	30 sec. (120 cards/hour) Max. 25 sec. (Max. 144 cards/hour)		
Laminating					
Laminating Mode			Single & Dual Lamination		
Laminating Film			0.6mil, 1.0mil (Clear & Holographic)		
_			Simultaneous: 23 sec. (YMCK, Single Lamination)		
			Simultaneous: 33 sec. (YMCKK, Single Lamination)		
Laminating Speed			One by One: 44 sec. (YMCK, Single Lamination)		
			One by One: 54 sec. (YMCKK, Single Lamination)		
Capacity			1		
nput Hopper Capacity	100 Cards	100 Cards	100 Cards	100 Cards	
Output Hopper Capacity	40 Cards	40 Cards	40 Cards	40 Cards	
System		10 00.00		10 00100	
Memory	64MB RAM	64MB RAM	64MB RAM	64MB RAM	
-	2 Lines LCD Display / 2 LED Buttons	2 Lines LCD Display / 2 LED Buttons		2 LED Buttons	
isplay & Control Panel Supported Platforms	Microsoft Windows 2000/2003/XP/Vista/7, Mac OS, Linux	Microsoft Windows 2000/2003/XP/Vista/7, Mac OS, Linux	2 Lines LCD Display / 2 LED Buttons Microsoft Windows 2000/2003/XP/Vista/7, Mac OS, Linux	Microsoft Windows 2000/2003/XP/Vista/7, Mac OS, Linux	
Communication	USB, Ethernet (Option)	USB, Ethernet (Option)	USB, Ethernet (Option)	USB, Ethernet (Option)	
Power Supply	Free Voltage (AC 110 / 220V, 50~60Hz)	Free Voltage (AC 110 / 220V, 50~60Hz)	Free Voltage (AC 110 / 220V, 50~60Hz)	Free Voltage (AC 110 / 220V, 50~60Hz)	
ower Consumption (Max)	48W	48W	96W	48W	
emperature / Humidity	15~35°C / 20~80%	15~35°C / 20~80%	15 ~ 35 °C / 20 ~ 80%	15 ~ 35℃ / 20 ~ 80%	
Dimensions					
Dimensions (W×L×H)	170mm x 420mm x 195mm	170mm x 510mm x 195mm	170mm x 900mm x 195mm	170mm x 420mm x 195mm	
Weight	4.5 Kg / 10 lbs	5.5 Kg / 12 lbs	9.2 Kg / 20 lbs	4.5 Kg / 10 lbs	
ncoding Options				-	
Magnetic	ISO 7811 (Track I, II, III Read/Write), HiCo / LoCo, JIS II	ISO 7811 (Track I, II, III Read/Write), HiCo / LoCo, JIS II	ISO 7811 (Track I, II, III Read/Write), HiCo / LoCo, JIS II	ISO 7811 (Track I, II, III Read/Write), HiCo / LoCo, JIS II	
Contact Smartcard	ISO-7816 (ID - 1)	ISO-7816 (ID - 1)	ISO-7816 (ID - 1)	ISO-7816 (ID - 1)	
Contactless Smartcard (Internal & External)	MIFARE, ISO 14443 (TYPE A/B), ISO 15693, DESFIRE, ICLASS	MIFARE, ISO 14443 (TYPE A/B), ISO 15693, DESFIRE, iCLASS	MIFARE, ISO 14443 (TYPE A/B), ISO 15693, DESFIRE, ICLASS	MIFARE, ISO 14443 (TYPE A/B), ISO 15693, DESFIRE, ICLASS	
Certifications	CE, UL, FCC, KCC	CE, UL, FCC, KCC	CE, UL, FCC, KCC	CE, UL, FCC, KCC	

Consumables

Color Ribbons				Security Films			
Ribbons Type	1	1		1	Films Type	ļ 🕴	1 1
	ҮМСКО	УМСКОК	YMCFKO	нумско		CPF	HPF
Cards / Ribbon	250	200	200	350	Cards / Film	250	250
Description	Full Color Ribbon with Resin Black and Overlay	Full Color Ribbon with Resin Black, Overlay and Resin Black for Back Side	Full Color Ribbon with UV Panel, Resin Black and Overlay	Half Panel Size Color Ribbon with Resin Black and Overlay	Description	Clear Patch Film	Hologram Patch Film
SMART-50S	0		0	0	SMART-50S		
SMART-50D	0	0	0	0	SMART-50D	_	_
SMART-50L	0	0	0	0	SMART-50L	ο	0

Mono Ribbons

Ribbons Type	ко	K	W	в	R	MG	MS	so
Cards / Ribbon	600	1200	1200	1200	1200	1200	1200	1200
Description	Black Monochrome Ribbon with Overlay	Black Monochrome Ribbon	White Monochrome Ribbon	Blue Monochrome Ribbon	Red Monochrome Ribbon	Metallic Gold Monochrome Ribbon	Metallic Silver Monochrome Ribbon	Scratch-Off Monochrome Ribbon
SMART-50S	0	0	0	0	0	0	0	0
SMART-50D	0	0	0	0	0	0	0	0
SMART-50L	0	0	0	0	0	0	0	0

