

SMART-30S is Value for Everyone!

www.idp-corp.com

Overlay •

UV Panel ●



Applications

- ID / Membership
- Access control / Security
- Healthcare
- Government
- Banking Card
- Transportation
- Retail
- Gift / Promotion / Loyalty

Features

- Color & Mono Printing
- Transparent Card with Magnetic Stripe
- Full Encoding Support (Magnetic, Contact, Contactless)
- Removable Stacker
- Compact Size



SMART-30S Specifications

Printing

Print Type

Print Area

Resolution **Dual Side Printing**

Card _

Card Feeding

Card Size

Card Thickness

Card Type

Print Speed

Monochrome **YMCKO**

Capacity Input Hooper

Output Hooper

System

Memory

Control Panel

Supported Platforms

Communication

Power Supply

Temperature / Humidity

Dimensions

Dimension (WxLxH)

Weight

Encoding Options

Magnetic

Contact Smartcard

Contactless Smartcard (Internal & External)

Certifications

SMART-30S (Single Side Card Printer)

Dye-Sublimation

Edge to Edge

300 dpi

O TBD

Automatic

O ISO CR80 (54mm x 86mm / 2.12" x 3.38")

0.38mm(15mil) ~ 0.76mm(30mil)

O PVC, Composite PVC, PET

5 sec. (720 cards/hour)

28 sec. (128 cards/hour)

0 80 cards

25 cards

64MB RAM

LED Button

Microsoft Windows 2000/2003/XP/Vista/7,

Mac OS, Linux

USB, Ethernet (Option)

Free Voltage (AC 110/220V, 50~60Hz)

Power Consumption (Max) • 48W

o 15~35°C / 20~80%

0 172 mm x 377mm x 190mm

0 3.4 kg / 7.5 lbs

O ISO 7811 (Track I, II, III Read / Write),

HiCo/LoCo, JIS II

O ISO 7816 (ID -1)

• MIFARE, ISO 14443 (Type A / B), ISO 15693, DESFIRE, iCLASS

O CE, FCC, KCC



 OFFICE Room 601, 7th Byuck-San Digital Valley, 170-13 Guro-Dong, Guro-Gu, Seoul 152-742, Korea

●T E L 82-2-6099-3700 ●F A X 82-2-6099-3717

E-mail sales@idp-corp.com



-32

Smart, Smarter than any other ID Card Printer

SMART-30S is value for ever



Telephone:+1 813-852-2010

Fax:+1 813-852-2523

E-mail: info@smarttechid.com www.smarttechid.com